



Lesoshoppe.com

your reliable & trusted business partner

Trade Portal For Test & Measurement Industry

For Reseller, please contact us for your discount.



SHIMADZU

UV-Vis Spectrophotometer Model: UV 1280



- Bandwidth: 5 nm
- Wavelength range: 190 to 1100nm
- Wavelength accuracy: ± 1 nm
- Wavelength reproducibility: ± 0.3 nm
- Wavelength slew rate: Approx. 6000 nm/min
- Photometric system: Monitor double-beam photometric system

SHIMADZU

220g x 0.1mg Analytical Balance Model: ATX224



The UniBloc's compact, uniform structure replaces 70 parts found in a conventional electromagnetic balance sensor assembly and ensures stable temperature characteristics, excellent response time and stable corner-load performance.

- Repeatability (Standard Deviation): ≤ 0.1 mg
- Linearity: ± 0.2 mg
- Pan Size (mm) approx.: $\Phi 91$
- Lockable, high-quality steel door

**Thermo
SCIENTIFIC**



Blood Bank Refrigerator Model: REB2304W



- Temperature Range: $+1^{\circ}\text{C}$ to $+8^{\circ}\text{C}$
- Forced air circulation for uniform temperature and fast door opening recovery
- Heat-free defrost for maximum uniformity
- Capacity: 385 liters
- Exterior Dimensions mm: 2012(H)x925(D)x711(W)
- Interior Dimensions mm: 1473(H)x 737(D)x610(W)
- Weight (kg): 213Kg

Hettich



Benchtop Centrifuge Model: Universal 320R



- Max. Capacity: 4 x 100ml / 32 x 1 ml
- Max. RPM: 15,000 Min -1
- Max. RCF: 21,382
- Running time: 1s - 99 Min : 59 Sec
- Package Include: 1624 Swing Out Rotor + 1742 Adapter (x4)

Kibron

Tensionmeters: Surface Tension - Precisely Model: EZ-Pi Plus



EZ-Pi plus is a new single channel tensiometer. EZ-Pi plus's full potential comes into action when pairing it up with a laptop. It is light-weight and robust and well suited for on-site measurements.

- Measuring range: 1-350mN/m
- Accuracy/sensitivity: better than 0.1mN/m
- Weight: 1.3kg
- Dimensions: 26x8x16 cm (10.2x3.1x6.3 in)
- Average time per measurement: Around 30 seconds

**VELP
SCIENTIFICA**

Velp FC6S 6 Position Flocculator Model: FC6S



- Product Type: Turbidity
- Power: 100/240 VAC
- Meter Style: Portable
- Individual settable speed, up to 200 rpm
- CE Compliance: Yes

THINKY

Planetary Centrifugal Vacuum Mixer Model: ARV-310



- Operation Time Setting: Timer setting range: 0 sec. to 30 min. in 1 sec. increments
- Continuous Operation Time: Max. 30 min.
- Programming Function: 9 recipe profiles with 5 steps.
- Vacuum System: Rotation section vacuum chamber system
- Ultimate Vacuum: 0.67 kPa / Approx. 5 Torr
- Unit Dimension: H450 x W555 x D645 (mm)
- Unit Weight: Approx. 90 Kg

Milwaukee

PH / Temperature Meter Model: Mi 150



3 years warranty

Memorized buffers 7

Self diagnostics

Dual Display

- Automatic Temperature Compensation (ATC) for good accuracy under fluctuating temperatures
- Easy and Quick Push-button Calibration
- 7 memorized buffers (pH 1.68, 4.01, 6.86, 7.01, 9.18, 10.01 and 12.45) for calibration

WELCH

Oil Free Vacuum Pump Model: 2534C-02



Green By Design

- Vacuum and Pressure : up to 60 Torr (27.6"Hg) and 106 Pascal (100 PSIG)
- Size: 34 L/min
- No Water or Oil
- Vacuum and Pressure Regulators and Gauges : simple to adjust, monitor vacuum level and delivery pressure

RaxVision

Fluorescent Research Microscope Model: E800MF



2 years warranty

5 years warranty anti-fungus

- Optical System: UIS (Universal Infinity System)
- Interpupillary distance: 48 - 75mm
- Eyepiece: High point and wide field eyepiece EW10X/20mm
- Objectives: Infinity plan-fluorescent 4X, 10X, 40X (Spring) and 100X (Spring)(Oil), infinity plan 4X, 10X, 40X & 100X (Oil)
- Double Layer Stage: 185mm(X) x 142mm (Y)
- Fluorescent Filter: Blue, green exciting light filter system and ordinary light system

AROS

Horizontal Measuring System Model: HIM-2015



- Travel-X,Y: 200 X 100mm
- Stage size: 200 X 120mm
- Magnification: 0.3x~1.8x (10x~60x) Step lens
- Linear scale: 0.5µm on X, Y-axis
- Length accuracy: $\pm (3+L/75) \mu\text{m}$
- Repeatability: 3µm

AccuTEC

Digital Counting Scale Model: UCA



2 years warranty

- High accuracy up to 1/30,000 resolution
- Rugged design with overload protector
- Large LCD with backlight display
- Long life rechargeable battery 160 hrs
- Hi-Lo check-weighing function available
- 285 x 240 mm Stainless Steel Weighing Pan
- UCA-B: 3Kg x 0.2g, 6Kg x 0.5g, 12Kg x 1g and 30Kg x 2g
- UCA-C: 3Kg x 0.1g, 6Kg x 0.2g, 15Kg x 0.5g and 30 Kg x 1g

Please visit our website at www.lesoshoppe.com for more information.

Download our free App now for Apples & Androids to stand a chance to win our monthly LUCKY DRAWS.



Lesoshoppe